

Technical data	FPKC 300	FPKC 500
Output cycles/minute	5	7-10
Max. case sizes	mm 500x400x400	
Set up power	8 Kw	12 Kw
Voltage	380 Volt	
Air consumption	300 l./min.	400 l./min.

- OPTIONAL**
- Multi-lane divider
  - Product guides adjustment by pantograph and handwheel

Line designed to pack various products in American (RSC) cases, ideal for limited spaces. Frame made of electro-welded and painted steel sections with adjustable feet; linear guideways for all mechanical movements. Safety guards of transparent polycarbonate with anodized aluminum frame. The line is composed of:

- Cardboard magazine with storing capacity of 150 to 200 folded cartons.
- Carton pick-up and opening by means of vacuum cups.
- Lower flap closing group.
- Adjustable boundary carton positioning device with plastic guides for a correct product centering, in alternative, centering device with quick changeover, for cartons with partitions.
- Transport conveyors of stainless steel with adjustable product guides (the conveyors are customized for different kinds of product).
- Adjustable gripper head with template, complete of anti-collision safety system.
- Upper flap closing group.
- Upper and lower taping group with relevant control photocells: width of the adhesive tape 50/70 mm. Quick and easy changeover operations by graduated hand-wheels and millimeter rules. Operator interface, for the management of the whole line, with control for start, stop, size change operations, manual movement, machine diagnostics, alarms and further visual and acoustic signals.

